

## I/O线缆-8芯PUR无屏蔽

		颜色代码	颜色示意	对应线芯
		BU		1
WH		2		
RD		3		
YE		4		
PK		5		
RD		6		
GY		7		
BN		8		
型号列表	L200/E324	L300/E324	L500/324	
型号规格	200米/盘	300米/盘	500米/盘	
技术参数				
产品结构	8C×0.25mm <sup>2</sup> (32/0.10B)	电气性能		
导体		额定电压	300V	
材料	裸铜	额定温度	-40...80℃	
尺寸	32/0.10±0.008mm	最大导体直流电阻 (20℃)	87.6Ω/km	
直径 (参考)	0.65mm	耐电压	AC 2.0kV/1min	
绝缘		物理性能		
材料	SR-PVC	抗张强度	≥10.3MPa	
最小平均厚度	0.23mm	断裂伸长率	≥100%	
最薄点	0.18mm	老化条件	113±1℃×168h	
直径	1.25±0.10mm	抗张强度保留率	≥70%	
成缆		断裂伸长率保留率	≥65%	
填充	PP绳	颜色规定		
材料	纸带	绝缘	1.蓝 2.白 3.红 4.黄 5.粉 6.绿 5.灰 6.棕	
护套		护套	灰色 RAL7001	
材料	PUR			
最小平均厚度	0.76mm			
最薄点	0.61mm			
直径	6.00±0.20mm			